



ROTARY PRESS HPM-600DA



FEATURES

Drum heater assures sufficient material heating from the every start of operation, just the same as flat type heating.

Temperature is automatically controlled by means of an electronic thermostat and SSR, and it maintains a sensitive thermostatic switch that turns on and off alternately, and the control temperature difference range is always within +/- 5°C

Uniformity and high pressure are maintained by a new air cylinder, a silicon rubber roller.

Anti-static type Teflon belts assures longer belt life, and belt cleaning and maintenance is easy made.

Belt warping Prevention Device maintains the belt at the same position at all time, so the operator needs only to insert the fabric.

SPECIFICATIONS

MODEL	HPM-600DA
Power Supply	3 phase
Heater rated out put	7.4 Kw
Motor rated out put	100W
Fusing width	600mm
Belt Speed	5.6m/min
Pressure	49N/cm(5.0kgf/cm)
Max temperature	195°C
Heating time	8-34sec
Dimensions	1325(L) X 1200(W) X 1100(H)
Weight	296kgs

STANDARD EQUIPPMENT

Belt Wrapping Prevention Device

Direct Roller Pressure System

Cooling Fan

Seamless Belt



Head Office
7-6, RYOGE, GIFU, JAPAN
TEL:81-58-245-4501
FAX:81-58-247-3366

Singapore Office
TEL:65-62858131
FAX:65-62858132